


CE MARKING - DECLARATION of PERFORMANCE (DoP)

No. DPL015 French Door Total70 Reinforced Escape Route 25/06/2013

Fabricator: Dessian Products LTD 9 Apollo Road □□ Adelaide Industrial Estate □□ Belfast Post code: BT12 6HP	Installers details to be added where frames sold unglazed	Installer: Enviro Windows & Cons UK Ltd 1 Rutherford Court □□ 15 North Avenue □□ Clydebank Business Park □□ Clydebank Post code: G81 2QP Or Registered No (5): Certass 0375003A
Window or Door	Door	
System	Total 70	
Style	French Doors (Open Out)	
Application & VACP	Class 1 (Escape Route)	
Authorised Representative		
Notified Body - hEN(4)		
Notified Body - ETA		
Test/certification body	BSI	KM 13358

Essential Characteristics acc. EN 14351-1: 2006 A1:2010

Resistance to Windload(3)	Class 2 (800 Pa)	
Resistance to Water(3)	Class 3A (100 Pa)	
Dangerous substances(1)	As per declaration by component suppliers	
Impact Resistance - doors	NPD	
Load bearing of safety devices(1)	NPD	350N if fitted
Height (Doors only)		
Operation forces (Automatic devices only)	NPD	
Acoustic Performance	NPD	
Thermal transmittance(1) (2) (3)	Minimum requirement (W/m <sup>2</sup> K)	Glazing requirement (W/m <sup>2</sup> K) Warm Edge $\Psi$ 0.04 - Metal $\Psi$ 0.06
	1.8	1.7 - 1.6
Radiation Properties	NPD	
Air Permeability(3)	Class 1 (150 Pa)	
Ability to release (Class 1 escape routes only)(1)		
Company Authorised Personnel - Fabricator	Name:	Dessian Products LTD
	Company Position:	Technical Manager
	Signature:	
	Date:	25/06/2013
Company Authorised Personnel - Installer	Name:	Yvonne Girvan
	Company Position:	Director
	Signature:	
	Date:	25/06/2013

Comments/notes:

(1) Threshold values must be entered - No Performance Declared (npd) acceptable for all other Essential Characteristic Values. (2) Thermal transmittance declared value dependant on fitting of specified glazing unit by manufacturer or named installer  
(3) Entry performance values declared where improved results may be available for specific applications. (4) Requirement for Notified Body approval of ITT & FPC for Class 1 doors (on escape routes)

Conditions for unglazed frames:

(5) Installers Registered No. - assigned by the fabricator. The fabricator must then hold details, on a register, which the installer signs to agree with the terms and conditions to which the declaration refers. It is the installers responsibility to ensure that the whole window conforms to the declared U value or better by sourcing a suitable glazing unit.